

# PLANNING AND SCHEDULING

Andrew Kusiak  
Intelligent Systems Laboratory  
2139 Seamans Center  
The University of Iowa  
Iowa City, Iowa 52242 - 1527

Tel: 319 - 335 5934      Fax: 319 - 335 5669  
*andrew-kusiak@uiowa.edu*  
<http://www.icaen.uiowa.edu/~ankusiak>



The University of Iowa

Intelligent Systems Laboratory

## Planning Hierarchy

Forecasting

- Forecasting

MPS

- Master Production Planning (Scheduling)

MRP

- Material Requirements Planning (MRP)



Balancing

- Capacity Balancing


Scheduling

- Production Scheduling



The University of Iowa

Intelligent Systems Laboratory



**MRP II (Manufacturing Resource Planning II)**

**ERP = MRP II + ...**




The University of Iowa

Intelligent Systems Laboratory

## History of ERP

- 1970's MRP Material Requirements Planning
- 1980's MRPII Manufacturing Resource Planning
- 1990's ERP Enterprise Resource Planning (e.g., SAP system)



**MRP II → ERP**


**Addition of CRM**



The University of Iowa

Intelligent Systems Laboratory

**Master Production Schedule**  
specifies  
**Sequence and Quantity of Products (C)**



**EXAMPLE**

Jan	Feb	March	Month
200 C1	195 C4	385 C1	
150 C7	150 C7	160 C6	
180 C14	180 C12	670 C7	
	128 C17	230 C9	



The University of Iowa

Intelligent Systems Laboratory

**ERP systems are used from**

- **Automotive industry**

**to**

- **Pharmaceutical industry**




The University of Iowa

Intelligent Systems Laboratory


# MRP ERP

Planning horizon:

1 month to  
3 day period



The BOM of Product C




**ERP**



The University of Iowa

Intelligent Systems Laboratory

## EXAMPLE: Material Requirements Records for the Spider Climber



The University of Iowa

Intelligent Systems Laboratory

## Merged Material Requirements for Aluminum Pipe

Aluminum pipe for leg supports										
	1	2	3	4	5	6	7	8	9	10
Gross requirements						20		30		
Projected on hand						0		0		
Net requirements						20		30		
Planned order receipts						20		30		
Planned order releases				20		30				

Aluminum pipe for ladder legs										
	1	2	3	4	5	6	7	8	9	10
Gross requirements				160		240				
Projected on hand				0		0				
Net requirements				160		240				
Planned order receipts				160		240				
Planned order releases	160		240							

Total aluminum pipe										
	1	2	3	4	5	6	7	8	9	10
Gross requirements				160		240	20	30		
Projected on hand				0		0	0	0		
Net requirements				160		240	20	30		
Planned order receipts				160		240	20	30		
Planned order releases	160		240	20		30				


MRP Record



The University of Iowa

Intelligent Systems Laboratory


## Basic Scheduling Models



The University of Iowa

Intelligent Systems Laboratory

# Single Machine Scheduling



The University of Iowa

Intelligent Systems Laboratory

## Scheduling n Operations on a Single Machine

Case 1: No constraints are imposed

### Theorem 1 (SPT Rule)

For a one-machine scheduling problem, the mean flow time is minimized by the following sequence:

$$t(1) \leq t(2) \leq t(3) \leq \dots \leq t(i) \leq \dots \leq t(n)$$

where  $t(i)$  is the processing time of the operation that is processed  $i^{\text{th}}$




The University of Iowa

Intelligent Systems Laboratory

## Example

Operation number	1	2	3	4	5	6
Processing time	4	7	1	6	2	3

SOLUTION: Gantt Chart of Single Machine  
Schedule (3, 5, 6, 1, 4, 2)



Flow time  $F_3 = 1$ ,  $F_5 = 3$ ,  $F_6 = 6$ ,  $F_1 = 10$ ,  $F_4 = 16$ ,  $F_2 = 23$

The mean flow time  $F = 9.83$  is minimum



The University of Iowa

Intelligent Systems Laboratory

# ?

## What does the minimization of the mean flow time imply?

Completing tasks with the minimum average flow time



The University of Iowa

Intelligent Systems Laboratory

## Case 2: Due dates are imposed

### Theorem 2 (EDD Rule)

For the one - machine scheduling problem with due dates, the maximum lateness is minimized by sequencing such that:

$$d(1) \leq d(2) \leq d(3) \leq \dots \leq d(i) \leq \dots \leq d(n)$$

where  $d(i)$  is the due date of operation that is processed  $i$ th



The University of Iowa

Intelligent Systems Laboratory

## Example

Operation number	1	2	3	4	5	6
Processing time	1	1	2	5	1	3
Due date	6	3	8	14	9	3



The University of Iowa

Intelligent Systems Laboratory



Operation number	1	2	3	4	5	6
Processing time	1	1	2	5	1	3
Due date	6	3	8	14	9	3

Operation Number	Due Date	Completion Time	Lateness	Tardiness
6	3	3	0	0
2	3	4	1	1
1	6	5	-1	0
3	8	7	-1	0
5	9	8	-1	0
4	14	13	-1	0

The optimal EDD schedule is (6, 2, 1, 3, 5, 4)

Operation 2 is late ( $L_2 = 1$ )



The University of Iowa

Intelligent Systems Laboratory

?

What does the minimization of the maximum lateness imply?

Elimination of long delays

&

More even distribution of delays  
(balancing delays)



The University of Iowa

Intelligent Systems Laboratory

## Classroom Exercise

- |             |    |    |    |
|-------------|----|----|----|
| • Job No.   | 1  | 2  | 3  |
| • Proc Time | 7  | 4  | 12 |
| • Due time  | 16 | 10 | 9  |

- Find SPT Schedule
- Find EDD schedule

SPT                    {2, 1, 3}

EDD                    {3, 2, 1}



The University of Iowa

Intelligent Systems Laboratory

## SCHEDULING MODELS


- Two-Machine Flowshop
- Two-Machine Job Shop
- Extensions



The University of Iowa

Intelligent Systems Laboratory

# Two-Machine Flowshop



Modified Johnson's Algorithm

Minimization of Max Flow (Min  $F_{\text{Max}}$ )



The University of Iowa

Intelligent Systems Laboratory

# ?

What does Minimization of the Max Flow (Min  $F_{\text{Max}}$ ) imply?

## Neutralizing outliers



The University of Iowa

Intelligent Systems Laboratory

## Two-Machine Flowshop Model

### Modified Johnson's Algorithm

- Step 1. Set  $k = 1, l = n$ .*
- Step 2. For each part, store the shortest processing time and the corresponding machine number.*
- Step 3. Sort the resulting list, including the triplets "part number/time/machine number" in increasing value of processing time.*
- Step 4. For each entry in the sorted list:*  
*IF machine number is 1, then*  
*(i) set the corresponding part number in position  $k$ ,*  
*(ii) set  $k = k + 1$ .*  
*ELSE*  
*(i) set the corresponding part number in position  $l$ ,*  
*(ii) set  $l = l - 1$ .*  
*END-IF.*
- Step 5. Stop if the entire list of parts has been exhausted.*



The University of Iowa

Intelligent Systems Laboratory

## Example: Two-Machine Flowshop Model

Schedule 7 parts

Two operations per part, each performed on a different machine

Part Number $i$	Processing Time $t_{ij}$ of Part $i$ on Machine $j$ $j = 1$	$j = 2$	Min	M
1	6	3	3	2
2	2	9	2	1
3	4	3		
4	1	8		
5	7	1		
6	4	5		
7	7	6		

For each part calculate  $\text{Min } \{t_{i1}, t_{i2}\}$



The University of Iowa

Intelligent Systems Laboratory

### Min processing time calculated

Part Number	$\min \{t_{i1}, t_{i2}\}$	Machine Number
1	3	2
2	2	1
3	3	2
4	1	1
5	1	2
6	4	1
7	6	2

### Triplets ordered on the processing time

(4, 1, 1)  
 (5, 1, 2)  
 (2, 2, 1)  
 (3, 3, 2)  
 (1, 3, 2)  
 (6, 4, 1)  
 (7, 6, 2)



The University of Iowa


Intelligent Systems Laboratory

(4, 1, 1)  
 (5, 1, 2)  
 (2, 2, 1)  
 (3, 3, 2)  
 (1, 3, 2)  
 (6, 4, 1)  
 (7, 6, 2)

Machine 1 →

← Machine 2

Optimal Schedule: (4, 2, 6, 7, 1, 3, 5)



The University of Iowa

Intelligent Systems Laboratory

?

Think of incorporating  
in Johnson's Algorithm

- ✓ Due dates
- ✓ Precedence constraints




The University of Iowa

Intelligent Systems Laboratory

## Two-Machine Job Shop

Use of Johnson's algorithm by  
dividing parts into four types



The University of Iowa

Intelligent Systems Laboratory

## Two-Machine Job Shop

Type A: parts to be processed only on machine M1.

Type B: parts to be processed only on machine M2.

Type C: parts to be processed on both machines in the order M1, M2.

Type D: parts to be processed on both machines in the order M2, M1.



The University of Iowa

Intelligent Systems Laboratory

### Algorithm

- Step 1. Schedule the parts of type A in any order to obtain the sequence SA.
- Step 2. Schedule the parts of type B in any order to obtain the sequence SB.
- Step 3. Scheduling the parts of type C according to Johnson's algorithm produces the sequence SC.
- Step 4. Scheduling the parts of type D according to Johnson's algorithm produces the sequence SD (Note that M2 is the first machine, whereas M1 is the second one).
- Step 5. Construct an optimal schedule as follows:

#### The Optimal Schedule

M1	(SC, SA, SD )
M2	(SD, SB, SC )



The University of Iowa

Intelligent Systems Laboratory

## Example: Two-Machine Job Shop

**Processing Time**

**Parts**

		First machine		Second machine	
1	M <sub>1</sub>	7	M <sub>2</sub>	1	
2	M <sub>1</sub>	6	M <sub>2</sub>	5	
3	M <sub>1</sub>	9	M <sub>2</sub>	7	
4	M <sub>1</sub>	4	M <sub>2</sub>	6	
5	M <sub>2</sub>	6	M <sub>1</sub>	6	
6	M <sub>2</sub>	5	M <sub>1</sub>	5	
7	M <sub>1</sub>	4	-	-	
8	M <sub>1</sub>	5	-	-	
9	M <sub>2</sub>	1	-	-	
10	M <sub>2</sub>	5	-	-	



The University of Iowa

Intelligent Systems Laboratory

**Parts**

		First machine		Second machine	
1	M <sub>1</sub>	7	M <sub>2</sub>	1	
2	M <sub>1</sub>	6	M <sub>2</sub>	5	
3	M <sub>1</sub>	9	M <sub>2</sub>	7	
4	M <sub>1</sub>	4	M <sub>2</sub>	6	
5	M <sub>2</sub>	6	M <sub>1</sub>	6	
6	M <sub>2</sub>	5	M <sub>1</sub>	5	
7	M <sub>1</sub>	4	-	-	
8	M <sub>1</sub>	5	-	-	
9	M <sub>2</sub>	1	-	-	
10	M <sub>2</sub>	5	-	-	

Type A: parts to be processed only on machine M1.

Type B: parts to be processed only on machine M2.

Type A parts: Parts 7 and 8 are to be processed on machine M1 alone. An arbitrary order SA = (7, 8) is selected.

Type B parts: Parts 9 and 10 require machine M2 alone. Select an arbitrary order SB = (9, 10).



The University of Iowa

Intelligent Systems Laboratory



**Parts**

	First machine		Second machine	
1	M <sub>1</sub>	7	M <sub>2</sub>	1
2	M <sub>1</sub>	6	M <sub>2</sub>	5
3	M <sub>1</sub>	9	M <sub>2</sub>	7
4	M <sub>1</sub>	1	M <sub>2</sub>	6
5	M <sub>2</sub>	6	M <sub>1</sub>	6
6	M <sub>2</sub>	5	M <sub>1</sub>	5
7	M <sub>1</sub>	4	-	-
8	M <sub>1</sub>	5	-	-
9	M <sub>2</sub>	1	-	-
10	M <sub>2</sub>	5	-	-

Type C parts: Parts 1, 2, 3, and 4 require machine M1 first and then machine M2.

### Type C Parts

Part Number	First Machine	Second Machine
1	7	1
2	6	5
3	9	7
4	1	6
Min {ti1, ti2}		
1	1	2
2	5	2
3	7	2
4	1	1
4	1	1
1	1	2
2	5	2
3	7	2

$$SC = (4, 3, 2, 1)$$



The University of Iowa

Intelligent Systems Laboratory

**Parts**

	First machine		Second machine	
1	M <sub>1</sub>	7	M <sub>2</sub>	1
2	M <sub>1</sub>	6	M <sub>2</sub>	5
3	M <sub>1</sub>	9	M <sub>2</sub>	7
4	M <sub>1</sub>	4	M <sub>2</sub>	6
5	M <sub>2</sub>	6	M <sub>1</sub>	6
6	M <sub>2</sub>	5	M <sub>1</sub>	5
7	M <sub>1</sub>	4	-	-
8	M <sub>1</sub>	5	-	-
9	M <sub>2</sub>	1	-	-
10	M <sub>2</sub>	5	-	-

Type D parts: Parts 5 and 6 require machine M2 first and then machine M1.

### Type D Parts

Part Number	First Machine	Second Machine
5	6	6
6	5	5
Min {ti1, ti2}		
5	6	1st(M2)
6	5	1st(M2)
6	5	1st(M2)
5	6	1st(M2)

$$SD = (5, 6)$$



The University of Iowa

Intelligent Systems Laboratory

Optimal Schedule

M1: (SC, SA, SD)

M2: (SD, SB, SC)

Partial  
Schedules

SA = (7, 8)

SB = (9, 10)

SC = (4, 3, 2, 1)

SD = (5, 6)

Optimal  
Schedule

M1: (4, 3, 2, 1, 7, 8, 5, 6)

M2: (5, 6, 9, 10, 4, 3, 2, 1)



The University of Iowa


Intelligent Systems Laboratory

## Optimal Schedule

M1: (4, 3, 2, 1, 7, 8, 5, 6)

M2: (5, 6, 9, 10, 4, 3, 2, 1)

### Gantt Chart of the Optimal Schedule



Min  $F_{\max} = 46$  for the optimal schedule



The University of Iowa

Intelligent Systems Laboratory

# ?

What is the main difference between

- ✓ Two machine flow shop schedule
- and
- ✓ Two machine job shop schedule



both solved with Johnson's algorithm?



The University of Iowa

Intelligent Systems Laboratory

## Answer: The Sequence of Operations



The University of Iowa

Intelligent Systems Laboratory

## Special Case of Three-Machine Flow Shop Model

Either 
$$\min_{i=1}^n \{t_{i1}\} \geq \max_{i=1}^n \{t_{i2}\}$$

or 
$$\min_{i=1}^n \{t_{i3}\} \geq \max_{i=1}^n \{t_{i2}\}$$

$$\begin{aligned} a_i &= t_{i1} + t_{i2} \\ b_i &= t_{i2} + t_{i3} \end{aligned}$$



The University of Iowa

Intelligent Systems Laboratory

## Example: Special Case of Three-Machine Flow Shop Model

### Scheduling Data

Actual Processing Times

Part	$t_{i1}$ M <sub>1</sub>	$t_{i2}$ M <sub>2</sub>	$t_{i3}$ M <sub>3</sub>
1	4	1	2
2	6	2	10
3	3	1	2
4	5	3	6
5	7	2	6
6	4	1	1



The University of Iowa

Intelligent Systems Laboratory

Actual Processing Times				Constructed Processing Times	
Part	$t_{i1}$	$t_{i2}$	$t_{i3}$	$a_i$	$b_i$
	$M_1$	$M_2$	$M_3$	First Machine	Second Machine
1	4	1	2	5	3
2	6	2	10	8	12
3	3	1	2	4	3
4	5	3	6	8	9
5	7	2	6	9	8
6	4	1	1	5	2

$$\begin{array}{ccc} 6 & 6 & 6 \\ \min_{i=1} \{t_{i1}\} = 3; & \max_{i=1} \{t_{i2}\} = 3; & \text{and } \min_{i=1} \{t_{i3}\} = 1 \end{array}$$

The first condition is met

$$\min_{i=1}^6 \{t_{i1}\} = 3 \geq 3 = \max_{i=1}^6 \{t_{i2}\}$$



The University of Iowa

Intelligent Systems Laboratory

Part Number	First Machine	Second Machine	Min {t <sub>i1</sub> , t <sub>i2</sub> }		
1	5	3	1	3	2
2	8	12	2	8	1
3	4	3	3	3	2
4	8	9	4	8	1
5	9	8	5	8	2
6	5	2	6	2	2

6	2	2
3	3	2
1	3	2
2	8	1
4	8	1
5	8	2

(2, 4, 5, 1, 3, 6)




The University of Iowa

Intelligent Systems Laboratory

## Gantt Chart of the Optimal Solution

Optimal Solution (2, 4, 5, 1, 3, 6)



The University of Iowa

Intelligent Systems Laboratory